

Electrification of a 40-ton electric mining vehicle

from vision to demonstration



Institut du véhicule innovant

Innovative Vehicle Institute



National Research
Council Canada

Conseil national de
recherches Canada



Institut du véhicule innovant

Innovative Vehicle Institute

Driver of innovation

The Innovative Vehicle Institute (IVI) is a Quebec-based center for innovation and applied research, affiliated with Cégep de Saint-Jérôme, and operates as a non-profit organization.

Our team assists companies and organizations in the **design and integration of innovative technologies** applied to vehicles and supports them in the **implementation** of their technology in real-life conditions.




ELECTRIC
VEHICLES



AUTONOMOUS
VEHICLES



CONNECTED
VEHICLES



Patrick Robitaille, P.Eng.
Electrical engineer - 8 years'
experience in electric vehicle
innovation

National Research Council

We are the government of Canada's research and development organization with over 100 years of experience.

National network of researchers and facilities performing research and technical services with partners

2,151

SCIENTISTS,
ENGINEERS,
TECHNICIANS, AND
OTHER SPECIALISTS

179

BUILDINGS
MANAGED

\$1.1B

ANNUAL
EXPENDITURE

1,577

R&D
COLLABORATIONS
AND HELPED 8,000
SMEs



Guillaume Imbleau
Chagnon, P.Eng.

Program Leader, Clean and Energy
Efficient Transportation

Project context


Mission:

- Development and integration of an electric propulsion system with a rapid charging infrastructure adapted to heavy vehicles in open-pit mining;
- Test the prototype in real world conditions to evaluate its suitability for open-pit mining operations.




40-ton Western Star 6900XD


Project timeline




Project stakeholders



Truck introduction



Preliminary drawing of the mining truck



Preliminary drawing of high voltage battery

Truck introduction

Vehicle :

- Vehicle weight : 30 920 kg
- Payload capacity : 29 801 kg
- Electric motor : 360 kW, 2050 Nm
- Original Allison 4500 RDS transmission
- Top speed : 70 km/h

Battery :

- 5x batteries at 82 kWh each
- Total capacity: 411 kWh
- Chemistry : NMC, pouch cell

Charging :

- Onboard AC Charger of 18 kW
- Compatible with CCS charger up to 475 kW



Test sequence

- Three-day test was completed at the Uniroc quarry site
- The goal was to cover two different seasons for comparison: fall and winter
- The three routes were different to reflect actual site operations

Result	Day 1 (November 17 2023)	Day 2 (December 7 2023)	Day 3 (March 1 2024)
Total round trip distance (km)	3.6	1.4	1.2
Maximum elevation (m)	58	30.4	85
Maximum incline (deg)	10.12	9.46	11.28
Outdoor temperature (°C)	10	-15	-11
Load (ton)	30	30	30



Day 1



Day 2




Day 3

Result – Vehicle Performance

- The truck's anticipated autonomy (100% DoD) varies by season:
 - Summer : ≈ 9.75 h
 - Winter : ≈ 7.83 h
- We are experiencing a notable loss of autonomy during winter months, with a decrease of around 19.7% compared to summer operations.
- Idle periods play a vital role in the overall performance of the truck.

Performance	Day 1 (November 17)	Day 2 (December 7)	Day 3 (March 1)
Estimated runtime with full battery usage (Hour)	9.75	7.03	8.62
Power consumption (kWh/km)	4.51	7.09	9.99
Ton moved per hour (T/h)	84.44	173.91	83.14
Idle period (%)	54.2	40.2	63.4




Result – Charging time

- The charger used at the quarry site was a Level 2 charger with a capacity of 19.2 kW
- The power of the charging station has a significant impact on vehicle downtime.
- With the current charging infrastructure used during the test, the vehicle was unable to operate daily.
- A 1-megawatt charger is excessive for the truck's usage in a quarry.
- >50 kW recommended for one 8 hours shift with 15 hours overnight recharge


Charging station	Level 2 charger (19.2 KW) (At winter temperature)	Level 3 charger 24 KW (At summer temperature)	Adria charger 1 MW (Estimated)
Charging time (h) (0-100 %SoC)	39.62	23.1	1-1,5

Usage cycle with a 19.2 kW charger



■ Recharge time ■ Operating time

Usage cycle with a 1 MW charger





■ Recharge time ■ Operating time

Result – Economic analysis

10-Year Cost Estimation

After a decade of operation, our estimate indicates:

- Diesel:
 - $\approx \$2,076,854$
- Electric truck with a 475 kw charger
 - $\approx 2\,471\,329$ \$ which is **+18.99 %** higher than the diesel truck
- Electric truck with a 50 kw charger
 - $\approx 1\,874\,422$ \$ which is **-9.75 %** lower than the diesel truck
 - The cost equivalence point is reached after approximately 7.7 years of operation.




Results – GHG emissions

67% reduction of overall lifecycle GHGs for operations in provinces with clean electricity grid

High influence of electricity grid emissions

Electric mining truck has higher manufacturing emissions

GHG reduction
~105 up to 215 tons per year




Lifecycle GHG emissions of Conventional (CMT) and Electrical (EMT) mining truck when operated in Quebec

Numerical tools for prototype design

Thermal models

- Experiment validated cell electrochemical-thermal model
- Integration of drive cycles demands
- Module thermal distribution with cooling strategy
- Vehicle instrumentation for thermal evaluation



Modules and cooling plate model



Battery pack instrumentation for thermal evaluation


Numerical tools for prototype design

Vehicle energy model


- Assess energy demands from specific mining operations

Life Cycle Analysis (LCA) model

- Estimate GHG emissions from manufacturing, operations and end of life activities




Main vehicle models for energy demand in operations



Boundary and key components for vehicle GHG assessment

New knowledge developed within the project


- Understanding and integration of heavy-duty batteries
- BMS architecture
- Reverse engineering
- Transmission operation with an electric motor
- Reality of mining and quarries
- Big data acquisition system



BMS architecture schematic

Lessons learned – project specific

- **Electrical utilities:** mining/quarry sites often fall short of the requirements for charging station operations.
- **Component failure:** experienced significant issues with rust on electronic boards within batteries.
- **Standard operations:** vehicle idling ~50% of operating window.



Rust on electronic boards

Lessons learned – recommendations

- **Standard operations:** utilizing idle times during operations for opportunistic charging could significantly increase autonomy and next-shift readiness
- **Optimal charging power:** clear understanding of operations to determine energy requirements -> minimize overall expenses (CAPEX, OPEX).
- **Demanding operations:** robust weatherproofing to avoid premature degradation of electronic components.

Average recoverable theoretical energy and range with opportunistic charging using idle time

Charging station power	Recovered energy (kWh)	Additional runtime (hours)
50 kW	48.7	0.99
1 MW	974	19.75

Conclusion

This project demonstrated how **heavy duty electric vehicles** could meet **operational and environmental objectives** in open pit mining.

Importance in **planning a charging solution** using **site specific operational requirements**

- Not a one size fits all and requires significant investment

Technology constantly improving: **Medium and Heavy Duty sector is the next electrification challenge**

Project partners



Institut du véhicule innovant
Innovative Vehicle Institute



National Research
Council Canada

Conseil national de
recherches Canada

propulsion
Québec

MMG

NOUVEAU MONDE GRAPHITE



TM4

ADRIA
POWER SYSTEMS®

Fournier



Natural Resources
Canada

Ressources naturelles
Canada

Canada



Thank you for your attention



Contact us



probitaille@ivisolutions.ca



guillaume.imbleauchagnon@cnrc-nrc.gc.ca

NRC-CNRC



Institut du véhicule innovant